



Technische Daten		STC-S-30	STC-S-41	STC-V-41	STC-S-51	STC-V-51	STC-S-61	STC-V-61
max. speed	rpm	1000	1000	750	1000	750	1000	750
Working Moment in kgcm Single Drive	min.	484	840	1200	1408	1160	2296	3592
	max.	890 1036***	1624	2316	2800	3108 3840***	4500	7600
Power Motor in kW *)		5,5	7,5	7,5	15	15	22	30
Total Weight in kg **)		464	531	582	876	912	1361	1572
Dimensions in mm								
	A	4x120	4x120	4x120	5x120	5x120	4x120	4x120
	A1	-	-	-	-	-	150	150
	B	260	260	260	300	300	390	390
	C	690	780	780	830	830	1040	1040
	D	158	182	182	175	175	260	260
	E	537	568	568	568	568	625	625
	F	Ø 31	Ø 25	Ø 25	Ø 31	Ø 31	Ø 31	Ø 31
	G	600	600	600	730	730	910	910
	H	310	310	310	315	315	370	370
	I	20	35	35	25	25	30	30
	K	616	651	779	905	905	1030	1090
	L	544	611	739	861	861	934	994
	M	340	340	340	380	380	470	470
	O	250	275	275	300	300	376	376
	P	632	667	795	917	917	1116	1116

- *) valid for single drive
 **) inclusive steel Unbalances
 ***) with lead mass

Dimensions may change
 October 2023

STC Screening Technology Consulting OHG
 Pinnaubogen 66
 D - 25482 Appen / Hamburg / Germany
 Tel. +49 4101 23434 / Mobil: +49 171 818 7244
 Fax +49 4101 200818
 E-Mail: info@stcserv.com
 Home: www.stcserv.com

Bank Connection:
 Sparkasse Suedholstein
 Kieler Strasse 1
 D - 24534 Neumünster
 BLZ 230 510 30
 Account. 30 42 660
 BIC/SWIFT: NOLADE21SHO
 IBAN: DE34 2305 1030 0003 0426 60