



Technische Daten		STC-S-30	STC-S-41	STC-V-41	STC-S-51	STC-V-51	STC-S-61	STC-V-61
max. Drehzahl in min ⁻¹		1000	1000	750	1000	750	1000	750
Arbeitsmoment in kgcm	min.	968	1680	2400	2816	2320	4592	7184
	max.	1780	3248	4632	5600	6216	9000	15200
Nennleistung Motor in kW *)		5,5	7,5	7,5	15	15	22	30
Gesamtgewicht in kg **)		460	520	550	910	1010	1300	1580
Abmessungen in mm	A	4x120	4x120	4x120	5x120	5x120	4x120	4x120
	A1	-	-	-	-	-	150	150
	B	260	260	260	300	300	390	390
	C	690	780	780	830	830	1040	1040
	D	Ø158	Ø182	Ø182	Ø182	Ø182	Ø260	Ø260
	E	537	568	568	580	580	621	621
	F	Ø 31	Ø 25	Ø 25	Ø 31	Ø 31	Ø 31	Ø 31
	G	600	600	600	730	730	910	910
	H	310	310	310	315	315	370	370
	I	20	35	35	25	25	30	30
	K	544	591	719	841	841	934	994
	M	340	340	340	380	380	470	470
	O	250	275	275	300	300	376	376
P	616	651	779	901	901	1030	1090	

*) gilt für Einzelantrieb
 **) inklusive Unwuchtgewichten

Änderungen vorbehalten
 Stand : 20. Juli 2014